

Cleaning - Protecting - Maintaining Quarry Tiles unglazed

Unglazed quarry tiles are extremely hard wearing and easy to maintain. Just rinsing the surface with water from time to time is not enough though - only the proper treatment ensures a well-maintained appearance even years from today.

Overview of the 3 Steps *for more detailed instructions, please refer to Page 2*

1

Initial cleaning of newly installed surfaces *used surfaces: Page 2*

Lithofin KF Cement Residue Remover cleans the surface and leaves it clear of all residues.



Coverage:
1Ltr./20m²



Dilute product 1:5
with water.




Distribute and allow
to work for 5 minutes,
then scrub.



Remove the solution
from the surface.



Rinse well with plenty
of clear water.



Allow to dry.

Please Note:
allow grout lines to
cure for several days
before cleaning. Pre-
wet the surface to
avoid damage to grout
lines.

Necessary equipment: bucket, mop and scrubber, squeegee or wet-and-dry vacuum

2a

Protecting against stains *initial cleaning of used surfaces: Page 2*


Lithofin KF Stain-Stop -invisible- protects against oil and water and simplifies maintenance.



Coverage:
1Ltr./15m²



Please note.




Pour product into
bucket or basin.




Evenly apply with a
brush or a roller.



Remove all excess
product from the
surface.



Allow to dry for
approx. 45 minutes.



Protect from water for
24 hours.

2b

Enhancing the appearance - indoor use only -

Lithofin KF Tile-Polish enhances the colour and produces an elegant sheen.



Coverage:
1Ltr./15m²

initial cleaning of used surfaces: Page 2

Necessary equipment: bucket, applicator or roller, brush, cloth

3

Regular maintenance


Lithofin EASY-CARE maintains tile surfaces..



Add one squirt (20ml)
to one bucket of
water.



Wipe surface with
solution. Do not rinse.



Allow to dry. Do not
walk on surface
during drying time.

Necessary equipment: bucket, mop

Please follow the detailed instructions on the product labels. *for additional information, please refer to Page 2*

Cleaning, Protecting, Maintaining unglazed Quarry Tiles

1 Cleaning and refurbishing used or extremely dirty surfaces

- ◆ Before treating used surfaces, the stone must be thoroughly cleaned. All deposits and care product residues must be removed from the surface and from the pores.
- ◆ **Indoors:** dilute Lithofin WEXA up to 1:3 with water and apply generously to the surface. Allow to work for 5 to 10 minutes.
- Brush well with a scrubber or a scrubbing machine and allow another 5 minutes working time.
- Add water while brushing and remove the solution from the surface.
- Rinse twice with clear water in order to remove all residues from the surface.
- ◆ **Outdoors:** in case of dark spots and stubborn dirt deposits, apply Lithofin MN Outdoor Cleaner with a scrubbing brush and allow to work overnight. Rinse off with plenty of clear water the next day.
- Allow the surface to dry for several days before applying the protective treatment.



Entfernen spezieller Verunreinigungen

| | |
|---|--|
| Cement residues, builders' dirt, calcium deposits | Lithofin KF Cement Residue Remover or Lithofin CEMENT-AWAY |
| tar, wax, varnish, paint, oil, grease | Lithofin WAX-OFF |
| stubborn oil stains | Lithofin OIL-EX |
| green deposits | Lithofin ALGEX |
| dirt deposits, alga growth, mould, etc. | Lithofin KF Mildew-Away or Lithofin MN Outdoor Cleaner |

2 Additional information about protective treatments

- ◆ Impregnators such as Lithofin KF Stain-Stop render the surface water and oil repellent.
- ◆ This protective effect prevents staining or at least simplifies removing stains.
- ◆ The surface becomes easier to maintain and stays beautiful for many years.
- ◆ Lithofin KF Stain-Stop provides optimal protection without altering the surface appearance.
- ◆ We recommend touching up the protective treatment after 4 to 5 years.
- ◆ Lithofin STAINSTOP >W< can be used as a water-based alternative.

Please note:

- ◆ **Always test the product in an inconspicuous area.** Non-absorbent or wet surfaces cannot be treated.
- ◆ Use impregnators only on completely dry surfaces. Otherwise, the product will not be able to penetrate into the surface.

3 Additional care

- ◆ Occasionally use Lithofin WEXA on surface subjected to heavy wear. Depending on the degree of dirt, add up to one litre to a bucket of cold water. Apply with a scrubbing brush and allow to work for 10 to 20 minutes. Do not allow to dry. Remove with a clean cloth and rinse with clear water.

Please Note:

△ Please follow the detailed instructions on the product labels.

△ This information should be considered to be informal and non-binding. The products must be used according to local conditions and materials. Instructions must be read carefully and followed closely. Where no previous experience is available, or in cases of doubt, test the product in an inconspicuous area. (GB5.06gps)